

1.2M KU-BAND


RX/TX

SERIES

1123 & 1125




Prodelin Corporation is the world's largest manufacturer of Rx/Tx VSAT antennas. We have the broadest product line in the industry including Receive Only, Rx/Tx and Rural Telephony antenna systems. Prodelin offers nineteen antenna sizes, 47cm to 4.5M. Prodelin is the leader in obtaining type certifications and approvals for Intelsat, AsiaSat and Eutelsat. Prodelin antennas provide the best quality in the market due to the sophisticated, precision SMC compression molding process technology. Prodelin provides the best value antenna solution to the market with competitive prices, the highest quality products and superb engineering support. Prodelin is ISO registered, KEMA # 70022.01. *Prodelin - The Market Leader in VSAT Antennas.*



Back View
Series 1123



Back View
Series 1125



Option
Feed Horn w/ OMT &
Transmit Reject Filter

Key Features

- Precision Compression Molded Offset Reflector
- Fully Galvanized Steel Mounts
- Optional Non-Penetrating Mast Mount Available
- Reflector/Feed Electrical Anti-Icing Available
- Low Cost Shipping and Easy Local Handling

[CLICK HERE to buy now](#)

Receive/Transmit
Series 1123 & 1125

1.2M KU-BAND

RX/TX

SERIES

1123 & 1125

Electrical		Series 1123 & 1125 Ku-Band
Antenna Size		1.2 M (48 in.)
Operating Frequency (GHz)	Receive	10.95 - 12.75
	Transmit	14.0 - 14.5
Midband Gain ($\pm .2$ dB)	Receive	41.7 dBi
	Transmit	43.2 dBi
Antenna Noise Temperature		
20° elevation		46 K
30° elevation		43 K
Sidelobe Envelope, Co-Pol (dBi)		
$1^\circ \leq \theta \leq 20^\circ$		29-25 Log θ
$20^\circ < \theta \leq 26.3^\circ$		- 3.5 dBi
$26.3^\circ < \theta \leq 48^\circ$		32 -25 Log θ
$48^\circ < \theta$		-10 dBi (averaged)
Feed Interface		Available in a variety of designs
Insertion Loss		0.2 dB max.
Cross-Pol Isolation		>30 dB (on axis)
VSWR		1.3:1 Max.
Mechanical		
Reflector Material		Glass Fiber Reinforced Polyester SMC
Antenna Optics		Prime Focus, Offset Feed
Mount Type		Elevation over Azimuth
Mast Pipe Size		2.5" SCH 40 Pipe (2.88" OD) 7.32 cm
Elevation Adjustment Range	<i>Series 1123</i>	<i>Series 1125</i>
	5° to 90° Continuous	12° to 90° Continuous
	Fine Adjustment	Fine Adjustment
Azimuth Adjustment Range	360° Continuous, $\pm 35^\circ$ Fine	360° Continuous
Shipping Specifications	83 lbs. (37.6 kg.)	61 lbs. (27.7 kg.)
Environmental Performance		
Wind Loading	Operational	50 mph (80 km/h)
	Survival	125 mph (201 km/h)
Temperature	Operational	-40° to 140° F (-40° to 60° C)
	Survival	-50° to 160° F (-46° to 71° C)
Rain	Operational	1/2" /hr
	Survival	2" /hr
Ice	Operational	-----
	Survival	1/2" radial
Atmospheric Conditions		Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas
Solar Radiation		360 BTU/h/ft ²



Post Office Box 1639
101 Eagle Road - Building #7
Avon, Colorado 81620 USA
970 748-3094 or tollfree 866 SATCOM1
Fax 970 748-3096
www.satcomresources.com



© Copyright 2000 Prodelin, a TriPoint Global Company.
All product specifications subject to change without notice.
The Prodelin logo is a trademark of TriPoint Global.